

---

## Release Notes - MC32N0 Android JB - BSP v00005 - HotFix CFE v00.01 Package

---

- [Introduction](#)
- [Component Description and Version](#)
- [Fixes/Security Patches Included](#)
- [Package Details](#)
- [Device Compatibility](#)
- [Installation Requirements](#)
- [Installation Instructions](#)
- [Release Date](#)

---

### ***Introduction***

HotFix CFE (Cumulative Fixes from Engineering) Package contains multiple SPR Hotfixes into a single package. The HotFix CFE Package helps the end users to keep up to date with all the SPR Hotfixes for given product software release / revision.

HotFix CFE packages are validated only by engineering validation team and the package follows Zebra Technologies HotFix Package Policy. Click here to view HotFix Package Policy. [HotFix Support Policy](#)

---

### ***Component Description and Version***

<b>Component / Description</b>	<b>Version</b>
<b>Product Build Number</b>	00-4AJ11-J-0000-0000-00-M1-033017
<b>Android Version</b>	JB 4.1.1
<b>Linux Kernel</b>	3.0.31
<b>Android SDK Level</b>	19
<b>Platform (TI/MPA/ etc)</b>	TI - OMAP 4430 - 4AJ11
<b>Bluetooth Stack</b>	4
<b>Partition Table</b>	NA
<b>Flash Size</b>	4 GB

<b>RAM Size</b>	1 GB
<b>MSP Package</b>	7.08.67
<b>Scanning Framework</b>	3.1.11
<b>DataWedge</b>	3.1.36
<b>Handwriting Recognition</b>	NA
<b>Moto Value Add (WR Components)</b>	3.5.1-1
<b>RxLogger</b>	2.0.0.50
<b>WiFi (TI)</b>	A_3.01.0.0.055
<b>GPS</b>	NA
<b>PTT</b>	3.1.20
<b>EA</b>	2.53
<b>SPAM</b>	4.7 (MV)
<b>SE965 Phase I firmware</b>	PAABPS00-001-R03
<b>SE965 Phase II firmware</b>	No firmware update required
<b>SE4750 Firmware</b>	CAABVS00-001-R01D0
<b>MobiControl Stage</b>	11.2.0.1143

## ***Fixes/Security Patches Included:***

### ***Fixes:***

The CFE package **CFE-MC32N0-J-xx-00005-x-00-01.zip** file includes the following HotFixes:

SPR31719 - Fixed an issue in which the WLAN radio fails to roam sometimes when Fast Transition (802.11r) is enabled on the infrastructure.

---

## ***Package Details***

**CFE-MC32N0-J-xx-00005-x-00-01.zip**

---

## ***Device Compatibility***

This HotFix CFE Package software release has been approved for use with the following Zebra devices.

<b>Device</b>	<b>Operating System</b>	<b>BSP Version</b>
MC32N0	Android JB Version 4.1.1	v00005

---

## ***Installation Requirements***

This SW is intended for the MC32N0 device running on BSP build 00-4AJ11-J-0000-0000-00-M1-033017 only.

---

## ***Installation Instructions***

1. Connect the USB cable from your PC to the device.
2. Copy the **CFE-MC32N0-J-xx-00005-x-00-01.zip** onto the root directory on a SD card.
3. Press and hold 1+9+Power Key. Unit will reboot at this point.
4. Release 1+9+Power keys and hold gun trigger while unit boots.
5. When Android logo appears on the screen release trigger key.
6. Press Home key to launch Recovery menu.
7. Use up and down arrows to navigate and enter key to select menu items.
8. Click on Vol+ or Vol- to navigate and select appropriated storage.
9. Select “apply update from sdcard”.
10. Select the **CFE-MC32N0-J-xx-00005-x-00-01.zip** file package on /sdcard.
11. When the update is completed select “reboot system now”

Note: battery must have at least 30% charge for the update to proceed.

---

***Release Date***

July, 2017

---