

---

# Release Notes <XT15/VH10 WinCE 6 OS Image><v12.6>

## Contents

---

[Description](#)

[Device Compatibility](#)

[Component Contents](#)

[Installation Requirements](#)

[Installation Instructions](#)

[Downloadable Software included in this Release](#)

## Description

---

The following changes and fixes have been included in this CFE:

SPR NO	Synopsis
32513	Fixed 5GHz Wi-Fi roaming algorithm to prevent connection attempts to incorrect SSIDs.
33477	Fixed Kiosk mode to allow hiding “Wi-Fi Config” Control Panel tabs.
33907	Updated Trigger Manager to allow selection of Push-To-Talk on VH10 vehicle mount computers with -600 MLB.

## Device Compatibility

---

This software release has been approved for use with the following Zebra devices.

Device	Operating System
Omnii XT15	Windows CE 6.0 Professional
Omnii XT15f	Windows CE 6.0 Professional
Omnii XT15ni	Windows CE 6.0 Professional
VH10	Windows CE 6.0 Professional

## Component Contents

---

N/A

## Installation Requirements

---

MicroSD card 2GB or greater formatted as FAT32 OR USB Memory stick and Omnii docking cradle

## Installation Instructions

---

To update the operating system software of the XT15/VH10, follow the procedure below:

1. The firmware can be upgraded using a USB Memory Stick or using a microSD Card.
2. The firmware file must be renamed 7545os.img
3. Copy the file containing the firmware upgrade to the root directory of the USB memory stick (XT15/VH10) or Micro SD card (XT15).
4. Install the USB memory stick into the docking cradle (or directly into the VH10) or install the Micro SD card into the XT15 in the Micro SD slot in the battery compartment.
5. On XT15, press and hold down the [Blue FN] key, the [SCAN] key and the [Power] key, simultaneously for a minimum of six seconds. On VH10, press and hold [Blue FN] key, the [SPACE] key and the [Red] key, simultaneously for a minimum of six seconds.
6. When the update is complete, the device reboots to the main operating system.
7. Remove the MicroSD card/USB memory stick from the device to prevent the device from performing the upgrade process again on the next cold boot, and then disconnect external power. The device is now ready to be used.

## Downloadable Software Included in this Release

---

Filename	Description
PV10XC60CPMI120600.IMG	7545 Windows CE OS image CFE Simplified Chinese v12.6
PV10XC60CTMI120600.IMG	7545 Windows CE OS image CFE Traditional Chinese v12.6
PV10XC60EFMI120600.IMG	7545 Windows CE OS image CFE ENG/FRA/GER/ITA/ESN v12.6
PV10XC60JPMI120600.IMG	7545 Windows CE OS image CFE Japanese

	v12.6
PV10XC60KOMI120600.IMG	7545 Windows CE OS image CFE Korean v12.6

Last Revised: 23/04/2018